



**YOU GET OUT
WHAT YOU
PUT IN.** 

4T Semi-Synthetic MB

Kendall® 4T Semi-Synthetic MB is a premium quality, part-synthetic engine oil designed primarily for use in 4-stroke cycle motorcycles, scooters, and all-terrain vehicles (ATVs). It also may be used as transmission oil in motorcycles and ATVs where the manufacturer specifies the use of motor oil in the transmission.

4T Semi-Synthetic MB is formulated to provide excellent wear protection, to minimize the formation of sludge and varnish, and to resist viscosity and thermal breakdown at high temperatures. It also protects against rust and bearing corrosion and is resistant to excessive foam buildup and air entrainment. The part-synthetic formulation provides additional thermal stability at high temperatures.

4T Semi-Synthetic MB meets the performance requirements of major motorcycle manufacturers and API Service SL. It meets JASO MB friction test requirements for use in motorcycle engines without integrated clutch and transmission.

Applications

- 4-stroke cycle motorcycles, scooters, and ATVs
- 4-stroke cycle gasoline engines in other mobile or stationary equipment where an API Service SL quality oil is specified

4T Semi-Synthetic MB meets or exceeds the requirements of and is approved for:

- JASO T 903:2011 Performance Classification MB

Features/Benefits

- Enhanced resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against scuffing and wear
- High shear stability
- Protects against rust and bearing corrosion
- Good resistance to foaming and air entrainment

**Part-Synthetic
Engine Oil for
4-Stroke Cycle
Motorcycles,
Scooters & ATVs**



4T Semi-Synthetic MB

Typical Properties	
SAE Grade	10W-30
Specific Gravity @ 60°F	0.868
Density, lbs/gal @ 60°F	7.23
Color, ASTM D1500	3.5
Flash Point (COC), °C (°F)	236 (457)
Pour Point, °C (°F)	-41 (-41)
Viscosity, Kinematic	
cSt @ 40°C	68.2
cSt @ 100°C	10.4
Viscosity Index	139
Cold Cranking Viscosity, cP	5,500
@ (°C)	(-25)
High Temp/High Shear Viscosity, cP @ 150°C	3.0
Sulfated Ash, ASTM D874, wt %	1.00
Total Base Number (TBN), ASTM D2896	7.6
Phosphorus, wt %	0.100
Zinc, wt %	0.110

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/SDS>

Updated: 11-26-2019

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

©Phillips 66 Company. Kendall® and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.