



**YOU GET OUT
WHAT YOU
PUT IN.** 

SHP® Synthetic Transoil 50

Kendall® SHP Synthetic Transoil 50 is a full-synthetic SAE 50 transmission lubricant designed for use in heavy-duty manual transmissions in trucks and buses operating in extreme temperatures and/or extended service intervals. It combines improved low-temperature properties with outstanding oxidation resistance and thermal stability at high temperatures to provide excellent all-weather, year-round performance.

SHP Synthetic Transoil 50 has excellent shear stability and antiwear properties to protect synchronizers, reduce component wear and promote longer transmission life. It is particularly recommended for use in newer, higher torque manual transmissions coupled with increased horsepower engines. It is recommended for extended drain service (up to 500,000 miles in linehaul service) in Eaton Roadranger® and Meritor transmissions

Premium Full-Synthetic SAE 50 Manual Transmission Fluid, API MT-1

Applications

- Heavy-duty manual and semi-automatic transmissions in trucks and buses where the OEM specifies a non-EP, API MT-1 SAE 50 or API GL-1 SAE 90 gear oil, or an SAE 50 heavy-duty engine oil

SHP Synthetic Transoil 50 meets or exceeds the requirements of:

- API Service GL-1, MT-1
- International (Navistar) TMS 6816
- Eaton PS-164 Rev 7
- Mack TO-A Plus
- Meritor O-81

Features/Benefits

- Extended drain, all-season performance
- Outstanding oxidation resistance and thermal stability to minimize sludge and varnish formation
- Excellent low-temperature properties for easier shifting in cold weather
- High shear stability
- High load-carrying capacity
- Protects against component wear and gear micropitting
- Protects against rust and corrosion
- Good foam resistance
- Excellent seal compatibility
- Potential fuel economy improvement compared with non-synthetic transmission fluids



SHP Synthetic Transoil 50

Typical Properties	
SAE Grade	50
Specific Gravity @ 60°F	0.860
Density, lbs/gal @ 60°F	7.16
Color, Visual	Amber
Flash Point (COC), °C (°F)	221 (430)
Pour Point, °C (°F)	-45 (-49)
Viscosity, Brookfield	7,000
cP @ -40°C	104,000
Viscosity, Kinematic	34.0
cSt @ 40°C	132
cSt @ 100°C	17.5
Viscosity Index	146

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/SDS>

Updated: 11-26-2019

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2016 Phillips 66 Company. Phillips 66 and its respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.