



**THE  
GOOD  
STUFF**

## **SHP® 295 ATF**

Kendall® SHP 295 ATF is a full-synthetic, heavy-duty automatic transmission fluid designed for use in truck and bus transmissions operating under severe service conditions or in extended drain intervals. It is particularly recommended by Phillips 66 Company for use in applications where the OEM specifies a fully approved Allison TES 295 fluid.

SHP 295 ATF has excellent shear stability and high load-carrying ability to protect against viscosity breakdown and wear. It has excellent oxidation resistance and thermal stability to minimize the formation of sludge and varnish, and excellent friction durability to ensure smooth shifting and proper transmission performance for the life of the fluid. It also has outstanding low-temperature properties for year-round use, and protects against rust and corrosion.

### **Applications**

- Heavy-duty automatic transmissions in trucks and buses in extended drain or severe service, such as in intracity transit buses, intercity tour coaches, school buses, emergency vehicles, recreational vehicles, refuse vehicles and commercial utility vehicles

SHP 295 ATF is OEM-approved for service fill in:

- Allison automatic transmissions where a TES 295 approved fluid is specified (approval no. AN-191011)

SHP 295 ATF is recommended for service fill in:

- Voith DIWA transmissions
- ZF Ecomat transmissions
- Applications recommending ZF TE-ML 04D/14C/16M/20C type fluids

### **Features/Benefits**

- Excellent friction durability for smooth shifting throughout the service interval
- Outstanding oxidation resistance and thermal stability for long fluid life
- Protects against sludge and varnish formation
- Protects against wear
- High shear stability
- Protects against rust and corrosion
- Outstanding low-temperature properties for easier shifting in cold weather
- Good seal compatibility
- Good foam resistance

**Allison TES  
295 Approved  
Premium  
Synthetic, Heavy-  
Duty, Automatic  
Transmission  
Fluid**



## **SHP<sup>®</sup> 295 ATF**

<b>Typical Properties</b>	
Specific Gravity @ 60°F	0.85
Density, lbs/gal @ 60°F	7.09
Color, Visual	Red
Flash Point (COC), °C (°F)	236 (456)
Pour Point, °C (°F)	-55 (-67)
Viscosity, Brookfield	
cP @ -40°C	8,500
Viscosity, Kinematic	
cSt @ 40°C	39.0
cSt @ 100°C	7.3
Viscosity Index	168
Zinc, wt %	<0.003

## **Health & Safety Information**

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/SDS>

12-20-18

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2016 Phillips 66 Company. Phillips 66 and its respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.